DEL 27 Plus COMFORT INSTANTANEOUS WATER HEATERS

Equip your home perfectly for anything

This series with 3i technology leads the way in terms of high hot water convenience. With its wide range of features, such as a backlit multifunction display, temperature memory, childproofing and ECO mode, this appliance boosts convenience levels for you in a multitude of ways.

Save energy at the press of a button

The energy and water saving ECO mode limits the maximum flow rate. You benefit from a constant supply of hot water, even at low inlet temperatures. And you reduce your water consumption without compromising on convenience.

Enjoy incredible ease of use

With the optional wireless remote control, you can very conveniently control your instantaneous water heater from a distance.

The main features

Instantaneous water heater with electronic closed-loop control

Accurate temperature delivery up to the appliance's output limit thanks to 3i technology

Sufficient hot water for multiple draw-off points

Particularly economical operation with ECO mode

Backlit multifunction display with output values



| _ | |
|---|--|
| | |
| Ö | |

DEL 18/21/24 Plus Product-No.: 236739

PRODUCT-NO.: 236740

Individual memory buttons for setting preferred temperatures

Adjustable temperature limit as anti-scalding protection for children

Can be combined with a wireless remote control



| Туре | DEL 18/21/24 Plus | DEL 27 Plus |
|----------|-------------------|-------------|
| Part no. | 236739 | 236740 |

Technical data

| Rated voltage | 400 V | 400 V |
|---------------------|------------------|------------|
| Rated voltage 1 | 380 V | 380 V |
| Rated voltage 2 | 400 V | 400 V |
| Rated output | 18/21/24 kW | 27 kW |
| Rated output 1 | 16,2/19/21,7 kW | 24,4 kW |
| Rated output 2 | 18/21/24 kW | 27 kW |
| Rated current | 29/31/35 A | 39 A |
| Rated current 1 | 27,6/29,5/33,3 A | 37,1 A |
| Rated current 2 | 29/31/35 A | 39 A |
| Fuse protection | 32/32/35 A | 40 A |
| Fuse protection 1 | 32/32/35 A | 40 A |
| Fuse protection 2 | 32/32/35 A | 40 A |
| Frequency | 50/60 Hz | 50/- Hz |
| Frequency 1 | 50/60 Hz | 50/- Hz |
| Frequency 2 | 50/60 Hz | 50/- Hz |
| Phases | 3/PE | 3/PE |
| Resistivity ρ15 ≥ | 900 Ω cm | 900 Ω cm |
| Conductivity σ15 ≤ | 1111 µS/cm | 1111 µS/cm |
| IP rating | IP 25 | IP 25 |
| Temperature setting | 20-60 °C | 20-60 °C |
| Colour | white | white |

| ON | >2,5 l/min | >2,5 l/min |
|-------------------------|------------|------------|
| Height | 466 mm | 466 mm |
| Width | 225 mm | 225 mm |
| Depth | 116 mm | 116 mm |
| Weight | 3.10 kg | 3.10 kg |
| Energy efficiency class | А | A |

Contact information

You have questions? We appreciate to help you: Call +49 5531 - 7020 Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.