

WATER

RUGGED

- 5-Year manufacturer's warranty
- Stored pressure design
- Polished stainless steel cylinders
- All-metal valve construction
- Exclusive crevice-free, butt-welded cylinder
- Temperature range -40°F to 120°F

USER-FRIENDLY

- Maximum visibility during discharge
- Large loop stainless steel pull pin
- QR coded and multilingual labels

OPTION

- Model 506B anti-freeze charge

MODEL 240 utilizes the cooling, soaking, and penetrating effect of a 45-55-foot stream of WATER. The 55-second discharge time makes it very effective for inexperienced operators for use on Class A fires that include combustibles such as wood, cloth, paper, and many plastics. This section is constructed with a chrome-plated brass valve and polished stainless steel cylinder, which helps eliminate corrosion.



240

THE MODEL 240 MAY BE FREEZE-PROTECTED TO -40°F
BY ADDING A MODEL 506B CHARGE

AGENT TYPE	WATER
DESIGN	Hose & Nozzle
MODEL NUMBER	240
UL & ULC RATING	2A
CAPACITY	2.5 Gal
SHIPPING WT. (LBS)	7.5
HEIGHT (IN.)	24.5
WIDTH (IN.)	9
DEPTH (IN.)	7
RANGE (INITIAL-FT)	45-55
DISCHARGE TIME (SEC.)	55
NOMINAL OPERATING PRESSURE	100 PSIG
INCLUDED BRACKET	Wall

**MANUFACTURED AND TESTED
TO UL STANDARDS**
COMPLIES WITH NFPA 10 STANDARD
ISO-9001/ISO-14001 CERTIFIED UL LISTED

CONFORMS TO TEST STANDARDS:
CAN/ULC-S507 - UL 626 &
CAN/ULC-S508 - UL 711



330.893.3139






www.holmesfireandsafety.com

















WHERE TO USE

AMEREX manufactures a variety of hand-portable and wheeled fire extinguishers, both “compliance” (code required) and “specialty” types.

“Compliance” extinguishers are designed to meet and exceed state or local fire protection requirements. “Specialty” extinguishers are intended for use on particular types of hazards so they should be placed in close proximity to the specific hazard they are meant to protect. It is natural for a person to use the extinguisher located nearest to a fire. The most current issue of NFPA-10 should be consulted for minimum recommended fire extinguisher types, placement, and travel distances. Your local Amerex Fire Equipment

Distributor is professionally equipped to help you evaluate and implement these recommendations. All “Pictograms” are detailed below and should be reviewed with all who might be expected to use a fire extinguisher. Everyone should be familiar with these picture symbols that identify the types of fires on which they may be used. The international sign system diagonal red slash indicates a potential danger if the extinguisher is used on that particular type of fire.

TYPES OF FIRES			
Class A	Ordinary combustibles	Wood, paper, rubber, fabrics, and many plastics	
Class B	Flammable liquids & gases	Gasoline, oils, paint, lacquer, and tar	
Class C	Live electrical equipment	Fires involving live electrical equipment	
Class D	Combustible metals or combustible metal alloys	Magnesium, titanium, potassium	
Class K	Fires in cooking appliance that involve combustible cooking media	Vegetable or animal oils, and fats	

Types of Extinguishers	
Class A	  
Class A:B	  
Class A:B:C	  
Class A:C	 
Class B:C	 
Class D	
Class A:K	 

HOW TO USE

All AMEREX extinguishers are furnished with a detailed “Owner’s Manual” containing valuable information on the installation, use, and maintenance of the extinguisher. The extinguisher nameplate contains specific information on “HOW TO USE” the particular extinguisher. The label instructions vary slightly according to type and size. Potential operators should be familiar with the instructions on any extinguisher they might be required to use.

