



## PURPOSE

The quick connect is used to connect two wireline components without the use of wrenches. The tool proves essential in the wireline industry as it enhances performance. It reduces making and breaking of thread connections on the tool string increasing safety and efficiency.

## ASSEMBLY PARTS

1. QC Pin to Threaded Box and Threaded Pin to QC Box
2. Spring
3. Lock Plate

## OPERATION

The crossover with the threaded pin should be attached to the tool string, and the crossover with the threaded box should be attached to the desired tool.

To join the Quick Connect, insert the Quick Connect pin into the Quick Connect box, compress the spring and turn 90 degrees to lock into place.

## QUICK CONNECT PIN TO THREADED BOX

Nominal Size		1.50"	1.75"
Item	Tread Size		
1	0.938 – 10 UN	0101COQ15002	0101COQ17503
2	1.062 – 10 UN	0101COQ15008	0101COQ17502
Top Thread Connection		QC PIN	1.75 QC PIN
Max O.D.		1.50"	1.75"
Fishneck size		1.375"	1.75"

## THREADED PIN TO QUICK CONNECT BOX

Nominal Size		1.50"	1.75"
Item	Tread Size		
1	0.938 – 10 UN	0101COQ150A0	0101COQ175A0
2	1.062 – 10 UN	0101COQ150A1	0101COQ175A1
Max O.D.		1.50"	1.75"
Fishneck size		1.375"	1.75"

\* Other sizes and combinations are available. \*