

OILFIELD, WIRELINE & DOWNHOLE TOOLS

JC-3 Running Tool



Scan for more information



Purpose

The JC-3 Running tool is used to run 1.50" O.D. gas lift valves into side pocket mandrels. It can be attached to kickover tools that utilize a 5/8" sucker rod connection in the kick arm designed for 1.50" valves.

The JC-3 Running tool is pinned to the gas lift valve and and utilizes a shear mechanism to release the valve after installing it into the side pocket mandrel.

Application:

• The JC-3 Running tool is typically used to run "R" or RA" type latches in "MM" Series Mandrels.

Key Features & Benefits:

- The tool is simple and robust consisting of only one part with no moving parts.
- It is available in a standard length and extended length version.





Technical Data		
Nominal Size	1.50"	1.50" - (5" Extended)
Assembly Number	02-04-JC-150-01	02-04-JC-150-02
Upper Thread Connection	0.938"-10 UN-2A	0.938"-10 UN-2A
Fishneck Size	1.375″	1.375″
Max O.D.	1.740"	1.740"
Overall Length	8.25"	13.25"
Latched Fishneck	1.375″	1.375"

Speak with a Brace Tool sales representative to explore the different configurations available on this tool and discover how we can match your requirements.



www.bracetool.com | Toll-Free: 1-800-438-0061.