

Version 1.4 | 04/13/2022




The Wave Standard Aluminum channel uses high quality 6063 aluminum. It is cost-effective and resistant to deformation and rust.

Dimensions (mm):





Tolerance: ±0.2mm



Note:

- 1. 2-L1 refers to two of symmetric L1 in each piece of profile.
- 2. (N-1)-L2 refers to (N minus one) of symmetric L2 in each piece of profile. "N" hereby stands for its corresponding "Hole Number" in the below table.

Part Number	Length	L1	L2	Slotted Hole	Hole Number
CL-16-R-AL-3C5-SD	35mm/1.38in	17.5mm/0.69in	/	4*10mm/0.16*0.39in	1
CH-16-R-AL-0M5-SD	500mm/19.68in	50mm/1.97in	200mm/7.87in	4*10mm/0.16*0.39in	3
CH-16-R-AL-01M-SD	1000mm/39.37in	100mm/3.93in	200mm/7.87in	4*10mm/0.16*0.39in	5
CH-16-R-AL-02M-SD	2000mm/78.74in	100mm/3.93in	200mm/7.87in	4*10mm/0.16*0.39in	10

UNITED KINGDOM

DISCLAIMER

GLLS, reserves the right to make any design changes for continuous improvement which will not affect the overall appearance or performance.

WEBSITES