SPOT CAM+

CHIRONIX >

BOSTON DYNAMICS

The Spot CAM+ payload turns Spot into a powerful inspection tool with purpose-built cameras and turnkey integration. Spot CAM+ features a color ring camera with a 360° field of view, for complete situational awareness while remotely operating the robot. A pan-tiltzoom (PTZ) color camera adds

a powerful 30x optical zoom, enabling detailed inspections from a distance. Integrated highsensitivity microphones and amplified speakers enable remote auditory inspections and two-way communications with operators in the field.



ENHANCED DRIVING EXPERIENCE

Get an immersive driving experience. Stream video from the camera to the tablet to confidently teleoperate around your site.



HIGH RESOLUTION DATA

Capture high quality color photos manually or on preplanned missions. Get eyes on remote or hazardous environments, focusing on inspection details that matter.



BUILT FOR DIRT AND DANGER

Drive with confidence through wet and dirty environments. IP65 sealed electronics for dust and water resistance enable this payload to go wherever Spot takes it.







SPECIFICATIONS

D	M	E١	12	10	NS	•
١		.				

	334 mm (13.1 in)
	203 mm (8.0 in)
(front mount)	330 mm (13.0 in)
(rear mount)	400 mm (15.7 in)
(front mount)	6.5 kg (14.3 lbs)
(rear mount)	7.0 kg (15.3 lbs)
	(front mount)

ENVIRONMENT

Ingress Protection IP65
Operating Temperature -20°C to 45°C

360° CAMERA

	300 CAMERA
360 x 170°	Panoramic Field of View
10MP	Panoramic Resolution
9600x4800	Panoramic Image Size
5x Sony IMX290	Panoramic Camera Sensor
2.16 mm	Panoramic Lens Focal Length
F2.0	Panoramic Lens Aperture
170°/sec	PTZ Range of Motion
-30 to 270°	PTZ Tilt Range
2MP	PTZ Resolution
1080p resolution video	
30x zoom	