



# PANTHERA HP METALLIZED

Panthera, emerging from leading PET lamination factories, offers unmatched stability and a substantial warranty. Its installer-friendly design ensures effortless application and uniform results. Enhanced with superior scratch resistance, it stands as the ideal solution for durable, easy installation and enduring window protection.

Width available in: 51, 76, 101, 152 cm

PROTECTOR



Panthera 295C → \*\*3 PLY & \*55μ / Panthera 298C → \*\*4 PLY & \*65μ

	Glare Reduction	Total Solar Energy Rejected	Visible Light Transmission
CLEAR WINDOW 3MM	<div><div></div></div> 9%	<div><div></div></div> 12%	<div><div></div></div> 90%
TINTED WINDOW 3MM	<div><div></div></div> 78%	<div><div></div></div> 34%	<div><div></div></div> 24%
PANTHERA 230C	<div><div></div></div> 29%	<div><div></div></div> 32%	<div><div></div></div> 70%
PANTHERA 255C	<div><div></div></div> 50%	<div><div></div></div> 39%	<div><div></div></div> 54%
PANTHERA 265C	<div><div></div></div> 65%	<div><div></div></div> 47%	<div><div></div></div> 36%
PANTHERA 275C	<div><div></div></div> 75%	<div><div></div></div> 54%	<div><div></div></div> 25%
PANTHERA 285C	<div><div></div></div> 85%	<div><div></div></div> 57%	<div><div></div></div> 16%
PANTHERA 295C	<div><div></div></div> 94%	<div><div></div></div> 59%	<div><div></div></div> 5%
PANTHERA 298C	<div><div></div></div> 97%	<div><div></div></div> 69%	<div><div></div></div> 3%

## CONSTRUCTION

- 1 Common scratch-resistant hard layer, allowing good durability and ease of maintenance when cleaning windows.
- 2 High-quality optical polyester, tinted in mass without optical distortion.
- 3 Bonding adhesive.
- 4 High-quality optical polyester, tinted in mass with anti-heat nano-ceramic particles.
- 5 PS adhesive, polymerizing with the glass within 15 days.
- 6 Adhesive protective liner, disposable after installation.

