

SG-2G-ELCC-KT

smartengine Universal Gateway for Emergency Lighting Kit



GENERAL SPECIFICATIONS

Brand	wtec
Product Type	Emergency Lighting smartgateway
Application	Enables ATS/UPS monitoring. Typical use is to meet UL924 listed Emergency Lighting requirements
Includes	Universal gateway for emergency lighting SG-2G-1RELAY-ELCC Wiring harness SG-2G-WH
Package Quantity	1

DIMENSIONS

Depth	106.68 mm 4.20 in
Height	30.48 mm 1.20 in
Width	76.20 mm 3.00 in
Weight	0.062 kg 0.14 lb

ENVIRONMENTAL SPECIFICATIONS

Environmental Space	Indoor Plenum
Safety Standard	AS/NZS CISPR 22 c-UL-us CE CEC Title 24-2008 IEC 60950 IEC 61000-4.5, Class 3 UL 60950 UL 924 UL-us US FCC Part 15, Class A

SG-2G-ELCC-KT

smartengine Universal Gateway for Emergency Lighting Kit

WIRING HARNESS

DIMENSIONS

Length	2 m 7 ft
Weight	0.73 kg 1.60 lb

MECHANICAL SPECIFICATIONS

Conductor Gauge, stranded	18 AWG
Conductors, qty	8
Contact Connector Interface	Stripped pigtail
Gateway Connector Interface	10-pin connector
Material Type	Copper

ENVIRONMENTAL SPECIFICATIONS

Environmental Space	Indoor Plenum
Flammability Rating	CMP NFPA 262 UL 910
Operating Temperature	0°C to +50°C (+32°F to +122°F)
Relative Humidity	10%-80%, non-condensing
Safety Standard	AS/NZS CISPR 22 c-UL-us CE CEC Title 24-2008 IEC 60950 IEC 61000-4.5, Class 3 UL 60950 UL 924 UL-us US FCC Part 15, Class A

REGULATORY COMPLIANCE/CERTIFICATIONS

Agency	Classification
RoHS 2011/65/EU	Compliant

