

## SG-2G-PLC220-KT

### smartengine Plug Load Gateway Relay Kit with wiring harness and RIB relay, 220 Vac



## GENERAL SPECIFICATIONS

Brand	wtec
Product Type	Plug Load smartgateway
Application	Enables plug load monitoring when connected to smartengine universal gateway
Includes	Universal gateway SG-2G-1RELAY   Wiring harness SG-2G-WH   Specified RIB
Package Quantity	1

## DIMENSIONS

Depth	38.10 mm   1.50 in
Height	43.18 mm   1.70 in
Width	81.28 mm   3.20 in
Weight	71.21 kg   2.80 lb
Wire length	406 mm   16 in

## ENVIRONMENTAL SPECIFICATIONS

Environmental Space	Indoor   Plenum
Safety Standard	AS/NZS CISPR 22   c-UL-us   CE   CEC Title 24-2008   IEC 60950   IEC 61000-4.5, Class 3   UL 60950   UL 924   UL-us   US FCC Part 15, Class A

## SG-2G-PLC220-KT

# smartengine Plug Load Gateway Relay Kit with wiring harness and RIB relay, 220 Vac

### LINE VOLTAGE / CURRENT

### REALAY EXAMPLES (LOAD DEPENDENT)

120-277V / 10A	RIBRELAY (RIB21CDC)
120V / 20A	RIBRELAY (RIB01BDC)
277V / 20A	RIBRELAY (RIB02BDC)

## WIRING HARNESS

### DIMENSIONS

Length	2 m   7 ft
Weight	0.73 kg   1.60 lb

### MECHANICAL SPECIFICATIONS

Conductor Gauge, stranded	18 AWG
Conductors, qty	8
Contact Connector Interface	Stripped pigtail
Gateway Connector Interface	10-pin connector
Material Type	Copper

### ENVIRONMENTAL SPECIFICATIONS

Environmental Space	Indoor   Plenum
Flammability Rating	CMP   NFPA 262   UL 910
Operating Temperature	0°C to +50°C (+32°F to +122°F)
Relative Humidity	10%-80%, non-condensing
Safety Standard	AS/NZS CISPR 22   c-UL-us   CE   CEC Title 24-2008   IEC 60950   IEC 61000-4.5, Class 3   UL 60950   UL 924   UL-us   US FCC Part 15, Class A

## SG-2G-PLC220-KT

smartengine Plug Load Gateway Relay Kit with wiring harness and RIB relay, 220 Vac

### RIB RELAY

### DIMENSIONS

Depth	38.10 mm   1.50 in
Height	43.18 mm   1.70 in
Width	81.28 mm   3.20 in
Weight	0.11 kg   0.24 lb
Wire length	406 mm   16 in

---

### REGULATORY COMPLIANCE/CERTIFICATIONS

Agency	Classification
RoHS 2011/65/EU	Compliant

