

B.

Select Home

Embrace the world of benefits provided by LVT with the ideal solution for residential areas: Select Home. With a 2mm thickness that includes a 0.15mm wear layer, it carries a 7-year residential warranty that is perfect for your home-sweet-home.

Extended Specifications

Type of Installation:	Dry Back (Stick Down)
Use Classification:	Moderate Domestic Use (Light Residential)
Total Mass:	4000 (g/m²) 117.97 (oz/yd²)
Wear Layer Thickness:	0.15 (mm) 0.005 (in)
Total Thickness:	2.0 (mm) 0.07 (in)
Tile Size (l x w):	1219.2 × 228.6 (mm) 9 × 48 (in)
Quantity Per Box:	15
Chemical Resistance:	Yes (EN ISO 26987)
Fire Classification:	Bfl-s1 (EN 13501-1)
Slip Resistance:	R10 (DIN 51130)



B.

Select Home

Extended Specifications

Residual Indentation:	<0.1mm (EN ISO 24343-1)
Dimensional Stability:	≤0.25% (EN ISO 23999)
Colour Fastness:	>6 Grade (ISO 105-B02)
Sound Absorption:	Approx. 3 dB (EN ISO 10140-3)
Castor Chair Suitability:	Yes, Type W (EN ISO 4918)
Floor Heating System:	Yes, max 27°C
VOC Emissions:	Floorscore SCS-FS-03336
Warranty:	7 years
Sustainability:	Floorscore



B.



Fab



Chic



Fine



Uber



Rad



Snazzy

Select Home



Bill of Quantities

- Belgotex’s SELECT HOME is available as ±2.0mm (total thickness) Moderate Domestic Use - Light Residential Dry back-stick down LVT vinyl.
- 1219.2 × 228.6mm with 0.15mm wear layer.
- 7 year residential warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.
- GreenTag Level A Gold Rated Certification.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.