

# B.

## Amble

A heterogeneous vinyl made for residential applications that boasts up to date designs. The homely and humble range knows exactly how people want to spend time with the floorcovering – at ease – and is an innovative vinyl product that is the perfect choice for the modern home. Offering a smooth, fashionable surface Amble is durable, water resistant and convenient, which makes it a practical flooring solution for kitchens, bathrooms and living rooms. And because heterogeneous vinyl is scratch-resistant and slip proof, it's perfect for families with young children or grandparents.

### Extended Specifications

|                       |                                    |                                  |   |
|-----------------------|------------------------------------|----------------------------------|---|
| Use Classification:   | Heavy Residential                  | Thermal Conductivity:            | 0.11 W/m.K (EN 12524)   |
| Type of Installation: | Heterogeneous Vinyl Sheeting       | Electrostatic Behaviour:         | ≤ 2kV (EN 1815)   |
| Overall Thickness:    | 2.7mm                              | Dimensional Stability:           | ≤ 0.4% (EN ISO 23999/EN 434)  |
| Wear Layer Thickness: | 0.25mm                             | Colour Fastness:                 | ≥ 6 Degree (EN ISO 105 B02)   |
| Product Width:        | 3m                                 | Sound Absorption:                | Δ Lw 13 dB (EN ISO 717/2)   |
| Backing:              | PowerBac                           | Dynamic Coefficient of Friction: | > 6 (EN 13893)  |
| Chemical Resistance:  | Resistant (ISO 26987/ EN 423)      | Underfloor Heating:              | Suitable (EN 12667)   |
| Fire Classification:  | Bfl-s1 (EN 13501-1)                | Castor Chair:                    | Note: Carpet Protector mats are necessary where castor wheels are used. |
| Slip Resistance:      | R10 (DIN 51130)                    |                                  |   |
| Residual Indentation: | ≤ 0.35mm (EN ISO 24343-1/EN 433)   |                                  |   |
| Thermal Resistance:   | 0.023m <sup>2</sup> K/w (ISO 8302) |                                  |   |





# B.



Algarve



Chapman



Havanna



Laurel



Oakland



Preston



Rockingham -  
776M




Tasmanian - 169M



Tasmanian - 790M

# Amble




Underfloor Heating



Heavy Residential



Natural Look



Suitable for Staircases




Power Bac



Anti-Bacterial



BN-S1



## Bill of Quantities

- Belgotex Amble 2.7mm heavy residential heterogeneous vinyl sheeting.
- 3m wide with 0.25 mm wear layer.
- 7-year residential warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.

\*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.