

B.

Strut

Strut is a heterogeneous vinyl made for heavy residential applications and boasting realistic designs. This uncompromising product speaks to confidence in materials and in how it deals with traffic, wear and scuffing. Part of a new generation of ready-to-install flooring, Strut is the perfect choice for the modern home as well as retail and hospitality spaces.

Offering realistic reproductions of wood and tile designs available in a sheet, this durable, water-resistant and convenient floor is easy to maintain, comfortable underfoot and soundproof. The heterogeneous vinyl is scratch-resistant and slip proof – perfect for families with young children or grandparents – while the hardy and hygienic PU layer is anti-allergenic, which makes it suitable for people living with allergies or pets.

Extended Specifications

Use Classification:	Heavy Residential / Medium Commercial
Type of Installation:	Heterogeneous Vinyl Sheeting
Overall Thickness:	2.8mm
Wear Layer Thickness:	0.4mm
Product Width:	4m
Backing:	Black Tex Bac
Chemical Resistance:	Resistant (ISO 26987/EN 423) Bfl-
Fire Classification:	s1 (EN 13501-1)
Slip Resistance:	R10 (DIN 51130)
Residual Indentation:	≤ 0.20mm (EN ISO 24343- 1/EN 433)
Thermal Resistance:	0.018m ² K/w (ISO 8302)

Thermal Conductivity:	0.16 W/m.K (EN 12524)
Electrostatic Behaviour:	≤ 2 kV (EN 1815)
Dimensional Stability:	≤ 0.4% (EN ISO 23999/EN 434)
Colour Fastness:	≥ 6 Degree (EN ISO 105 B02)
Sound Absorption:	Δ Lw 15 dB (EN ISO 717/2)
Dynamic Coefficient of Friction:	> 6 (EN 13893)
Underfloor Heating:	Suitable (EN 12667)
Castor Chair:	Note: Carpet Protector mats are necessary where castor wheels are used



B.



Columbian Oak - 910M



Columbian Oak - 649M



Gambel Oak - 119M



Laurel Oak - 116L



Laurel Oak - 669D



Nottingham - 119M



Rockingham - 790M



Tasmanian Oak - 096L



Texas Oak - 136L



Texas Oak - 162L



Zinc - 096L



Zinc - 996D

Strut



Underfloor Heating




Medium/General Commercial



Heavy Residential



Natural Look



Suitable for Staircases




Comfort Bac



Anti-Bacterial



BN-S1



Bill of Quantities

- Belgotex Strut 2.8mm heavy residential/medium commercial heterogeneous vinyl sheeting.
- 4m wide with 0.4 mm wear layer.
- 10-year residential warranty and 5-year commercial warranty.
- This product is to be laid in accordance with SANS 10070 fitting code of practice.
- Belgotex recommends the use of a 60mm unhooded soft castor, with a 23mm or 38mm diameter, designed for a 60kg loading capacity per a castor. Recommended material is high impact nylon core and hub with soft grey/black PU treads on the wheel.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd. © BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.