



# Harmony Direct gen 1.5 (Int.)

Multi-standard DC charger  
for multiple EV types

120 – 180 kW DC Charging Station



# Power up your charging operations

Serving all types of vehicles and charging needs, our Harmony fast DC chargers guarantee smooth backend compatibility, an intuitive user experience, and simple integration with your existing business operations.



## Everything you might be asking for

- + Operable in extreme high temperatures without power derating
- + Cable management retractor and integrated area lighting
- + CCS2, CHAdeMo, GB/T outputs
- + >95% energy efficiency
- + Power configurations from 120 kW to 180 kW in 30kW increments
- + Stainless Steel structure available
- + Smooth payment and authentication
- + Intuitive user experience
- + Authentication: RFID, QR code, Plug & Charge with MAC ID
- + OCPP 1.6J
- + Easy transportation and installation
- + Customizable corporate branding
- + 10" capacitive touch screen user interface
- + IP54 rated water resistant

## The trusted EV charging solution provider for industry leaders

### Fleets

Fleet vehicles only earn you money while they're on the road. We help ensure your vehicles are charged and ready for work whenever and wherever they're needed.

### Workplace

Exercise your commitment to sustainable transportation and facilitate company-wide emission reduction by providing convenient workplace charging options.

### Charge Point Operators

End-to-end management and control over the charging process and experience. Pair your chargers with ChargeX or integrate with another charger management system of your choice.

### Retail & Hospitality

Reliable charging solutions that are easy to install, maintain, and scale, so you can appeal to EV-driving patrons with convenient on-site charging options.

### Heavy duty vehicles

Big loads need powerful charging. Our industrial charging solutions ensure your heavy duty fleet is charged and ready to run at full capacity.

## The trusted EV charging solution provider for industry leaders



# Specifications



## Power Output

**DC Output Voltage Rating:** 200 – 1,000 Vdc

**Outlet 1:** CCS-2 200 A or 250 A or 300 A or 400 A (cont.), GB/T 200 A or 250 A (cont.)

**Outlet 2 (optional):** CCS-2 200 A or 250 A or 300 A or 400 A (cont.), GB/T 200 A or 250 A (cont.), CHAdeMO 125 A

**System Power Rating:** 120kW with 4\* 30kW modules

150kW with 5\* 30kW modules

180kW with 6\* 30kW modules

**CCS Power Class:** UFC 120, UFC 150, UFC 180

**Simultaneous EV charging qty.:** up to 2

## Mains Input

**Input Voltage (nominal):** 380/400/415 Vac

**Input Voltage Range:** 320 Vac – 520 Vac

**Network Connection:** TN-S

**AC Wiring:** 3-Phase (L1, L2, L3), N, PE

**AC Power Rating (@ 400 Vac):** 186 A, 129 kVA for 120 kW

235 A, 161 kVA for 150 kW

280 A, 194 kVA for 180 kW

**Input Frequency (nominal):** 50 / 60 Hz

**Input Frequency Range:** 45 – 65 Hz

**Conversion Efficiency:** ≥ 95% (peak)

**THD(i):** < 5 %

**Power Factor:** > 0.98

**Inrush Current (Instant Impulse Current):** < 100 A

**Short Circuit Current Rating:** 25 kA

**Standby Power @ nom. voltage:** <35W

## Mechanical

**Ingress Protection:** IP 54 acc. IEC 60529

**Impact Resistance:** IK10 acc. IEC 62262

**Dimension (H\*W\*D):** 1,850 \* 650 \* 630 mm without cable management (2,005 mm height with cable management)

**Weight:** 350 kg Approx.

**Cable Management (option):** Roof mounted sprung retractors with integrated area/status lighting

**Charging Cable Length:** 5 meters, 7 meters optional

**Material:** Texture Finish Powder Coating SECC or Stainless Steel

**Mounting:** Free Standing (may be bolted to floor)

**Cooling:** Forced Air (variable speed)

## Configuration

**Software update:** OTA (Over The Air)

**Control and Set up:** OCPP v1.6j, local, Exicom MBE platform (password controlled)

## Environmental

**Operating Temperature:** -30 °C to 75 °C (linear de-rating above 55 °C)

**Storage Temperature:** -40 °C to 80 °C

**Altitude:** 2,000 meters (de-rating above 2,000 meters)

**Humidity (Non-Condensing):** 5 % to 95 %

# Specifications



---

## Standards / Certification

**Safety:** IEC 61851-1;  
IEC 61851-21-2; IEC 61851-23; IEC 61851-24; IEC 62196-1; IEC 62196-2; IEC 62196-3; IEC 61000  
**Other:** CE (LVD, EMCD, RED, ROHS); ARAI (AIS 138 Part 2)  
**Vehicle Communication:** DIN 70121, ISO15118, CHAdeMO v1.2, GB/T 27930

---

## Quality

**Mean Time Between Failure:** >150,000 hours  
**Mean Time To Repair:** <1 hour on arrival at site  
**Design Life:** 10 years\*  
**Warranty:** 2 years\* (standard). Extension available

---

## Protection and Safety

**Surge Protection:** Integrated – IEC 61000-4-5  
**Over Current:** 101 A @ 300 Vdc per 30 kW module  
**Under Voltage:** AC Input: < 280 Vac phase to phase  
**Over Voltage:** AC Input: > 530 Vac phase to phase  
**Over Temperature:** Auto de-rated above 55 °C ambient  
**Residual Current (Leakage):** < 30 mA  
**Over Voltage Category:** III

---

## User Interface and Comms

**Display:** Integrated – 10" capacitive touch screen TFT LCD  
**Support Language:** Multi-language  
**Emergency Switch:** Available (red mushroom push button)  
**Charge Option / User Authentication:** RFID, mobile app, OTP, QR Code  
**Energy Metering:** DC Included (EN50470-4 compliant option)  
**Visual Indication (LED):** Presence of Supply, State of Charging, Error  
**RFID:** MIFARE – ISO/IEC 14443A/B  
**Connectivity:** Internet access via Ethernet (RJ45)  
**Modem (option):** 4G LTE (EU)

\* Terms and Conditions apply

1

2 3

4 5

6.1 6.2

7.1

7.2

8

9

10

# harmony D 180 K 1K0 - 2 2 - 250 - 250 - 30a - G15180 - XX

1	Family Name:	Harmony	7	Max Gun Rating (A):	200 = 200 A; 250 = 250 A; 300 = 300 A; 400 = 400 A
2	Type:	D = Harmony Direct	8	Module Type:	30a = 30kW (std)
3	Power Rating:	60 = 60kW; 120 = 120 kW; 150 = 150 kW; 180 = 180 kW	9	Frame Size:	G15180 = Gen 1.5, 180kW cabinet
4	Fixed Text:	K = 'thousand'	10	XX:	Specific Variant - Consult Exicom
5	Output Voltage:	1K0 = 1,000 Vdc			
6	Connector config:	2 = CCS2; 3 = CHAdeMO; 4 = GB/T-12; 5 = GB/T-24; BLANK = NONE			

THIS DOCUMENT CONTAINS INFORMATION THAT IS SUBJECT TO CHANGE WITHOUT NOTICE.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including, but not limited to, copying, recording, retrieving data, or computer networks without the written permission of Exicom.

Exicom and all other Exicom product names and slogans are trademarks or registered trademarks of Exicom. Exicom products can be protected by one or more patents.

All other products and services mentioned may be trademarks or service marks of their respective owners.

Illustrations of the product and user interface are exemplary and may differ from the actual appearance.

March 2024 – Version 3.0 (int)

© 2024 by Exicom. All rights reserved



Scan for

Digital Brochure



EV chargers for homes  
and businesses

Exicom is distributed and maintained by a  
network of qualified partners and resellers.

Find more information and your local partner at:

[exicom-ps.com](https://exicom-ps.com)