

[Click Here](#)



===== RCC structures are primarily composed of reinforced concrete elements such as footings, columns, beams, slabs, and staircases. These components provide stability to the structure, thanks to the reinforcement with steel. The staircase is a crucial component in any RCC structure. In this article, we will explore various types of staircases and focus on the dog-legged reinforced cement concrete staircase design. Stairs serve as a vital means of accessing different floors in a building. As a result, their location must be carefully considered to provide efficient access between floors. In residential buildings, staircases are typically placed near the main entrance. On the other hand, public buildings require stairs to be centrally located near the main entrance for quick accessibility to principal apartments. It is essential that all staircases are adequately lit and well-ventilated. Proper lighting prevents accidents, while ventilation ensures a comfortable environment for users. The dog-legged staircase design is characterized by its unique layout, where succeeding flights rise in opposite directions. The two flights in plan are not separated by a wall; instead, a landing is provided at the level where the direction of the flight changes. Staircases can be classified based on the direction along which the stair slab spans. There are three types: horizontally spanning stairs, vertically spanning stairs, and longitudinally spanning stairs. Horizontally spanning stairs are supported at each side by walls or at one side by a wall and at the other side by a beam. Vertically spanning stairs, on the other hand, are supported solely by beams or stringers at both ends. When designing an RCC stair, it is crucial to analyze the various loads that will be imposed on the structure, including dead load, live load, and floor finish. The strength of the staircase is determined by the ratio of steel to concrete used. Steel takes up tension, while concrete bears compression. In multi-storey buildings, ramps, elevators, escalators, and stairs are often employed to facilitate vertical circulation. Stairs provide essential vertical circulation and access across different floor levels in a building. It is recommended that when an access height exceeds 600mm, a staircase should be provided. Modern architecture emphasizes the aesthetic appeal of stairs, making them an integral part of a building's interior beauty. There are various types of stairs with distinct configurations, including straight flight staircases, circular staircases, helical staircases, spiral staircases, and combinations thereof. The recommended slope for comfort is 27°, although it can be extended to 35° for practical purposes. Straight stairs are typically arranged in a single flight between two successive floors or levels, with various possible configurations. =====Staircase Structure and Design Guidelines ===== Helical Stairs are a type of spiral staircase that follows a curved path with multiple centres of curvature. ===== Attention should be paid to the optimal line structure and reinforcement when detailing staircases, particularly at points of high-stress concentration. Typically, additional bars are included to prevent crack formation in these areas. A well-detailed corner (edge between flight and landing) is shown below; additionally, detailed end supports for staircases with landings are also depicted. A staircase's 'three-dimensional' nature and stiffening effect of triangular tread areas often lead to actual stress distributions differing from those calculated, which should be kept in mind during detailing. The typical pattern of internal stresses induced in a simply supported straight flight stair and reinforcement pattern is illustrated. Simple straight flights can span either transversely (across the flight) or longitudinally (along the flight). When spanning transversely, supports must be provided on both sides of the flight by walls or stringer beams. In this case, the waist or thinnest part of the stair construction need only be 60 mm thick, as it is the effective lever arm for resisting bending moment. In principle, design requirements for beams and slabs also apply to staircases; however, designers cannot accurately determine deflections in complex stair types. BS 8110 only deals with simple systems and allows a modified span/effective depth ratio to be used. Bending moments should be calculated from the ultimate load due to total weight and imposed loads, measured on plan, combined with horizontal span. Stresses produced by longitudinal thrust are small and generally neglected in simple system design. A section of a staircase is shown above, with dimensions including width 1160mm, expected carrying capacity, and structural idealisation data such as density of concrete (25 kN/m³), compressive strength of concrete (30 N/mm²), and yield strength of steel (460 N/mm²). ===== The formula provided can be simplified as: $M_{Ed} = (41.119 \times 106)/(30 \times 1000 \times 1692) = 0.0479$ Since $k < 0.167$, no compression reinforcement is required. $z = d[0.5 + \sqrt{(0.25 - 0.882k)}] = z = d[0.5 + \sqrt{(0.25 - 0.882 \times 0.0479)}] = 0.95d$ $A_{s1} = M_{Ed}/(0.87fykz) = (41.119 \times 106)/(0.87 \times 460 \times 0.95 \times 169) = 639.96 \text{ mm}^2/m$ To calculate the minimum area of steel required, we need to follow these steps: $f_{ctm} = 0.3 \times f_{ck}(2/3) = 0.3 \times 30/23 = 2.896 \text{ N/mm}^2$ (Table 3.1 EC2) $A_{s,min} = 0.26 \times f_{ctm}/f_{yk} \times b \times d = 0.26 \times 2.896/460 \times 1000 \times 169 = 276.631 \text{ mm}^2/m$ Checking if $A_{s,min} < 0.0013 \times b \times d$ ($219.7 \text{ mm}^2/m$), we get: Since, $A_{s,min} = 276.631 \text{ mm}^2$, the provided reinforcement is adequate. $k = 1.0$ for simply supported beams and slab $\rho = A_s/bd = 753/(1000 \times 169) = 0.004455 < 10\text{-}3/30$ $L/d = k[11 + 1.5\sqrt{(f_{ck})\rho/p} + 3.2\sqrt{(f_{ck})\rho/p} - 11.5)]/d = 1.0[11 + 1.5\sqrt{30 \times (0.005477/0.004455)} + 3.2\sqrt{30 \times (0.005477/0.004455)} - 11.5] = 1.0(21.1 + 1.9258) = 23.0258$ Modification factor $\beta_s = 310/(\sigma_{s,req}/(500A_s,prov)) = (310 \times 460 \times 639.96)/(500 \times 753) = 242.358$ N/mm^2 $\beta_s = 310/242.358 = 1.2789$ Taking the distance between supports as the effective span, $L = 4.35m$ Allowable span/depth ratio = $\beta_s \times 23.0258 = 1.2789 \times 23.0258 = 29.460$ Actual deflection $L/d = 4350/169 = 25.739$ Since $25.739 < 29.460$, deflection is ok. Ultimate shear force $V_{Ed} = 35.358 \text{ kN} = V_{Ed}/bd = (35.358 \times 1000)/(1000 \times 169) = 0.209 \text{ N/mm}^2$ $VR_{d,c} = [CR_{d,c}k(100\rho f_{ck})^{1/3}] \geq (V_{min})/CR_{d,c} = 0.18/\gamma_c = 0.18/1.5 = 0.12k = 1 + \sqrt{(200/d)} = 1 + \sqrt{(200/169)} = 2.087 > 2.0$, therefore, $k = 2$ $V_{min} = 0.035k1.5f_{ck}0.5V_{min} = 0.035 \times 21.5 \times 300.5 = 0.5422 \text{ N/mm}^2$ $\rho_1 = A_s/bd = 753/(1000 \times 169) = 0.0044556 < 0.02VR_{d,c} = [0.12 \times 2(100 \times 0.0044556 \times 30)^{1/3}] = 0.569 \text{ N/mm}^2$ Since $VR_{d,c} > V_{Ed}$, no shear reinforcement is required. Shear is ok. Staircase Characteristics and Design Considerations ===== The radius of curvature for a small-stair design might necessitate column support, whereas stairs function by employing various structural components. These include flight elements consisting of multiple steps connecting different floors or levels. Functional Components of a Staircase # Flight A series of connected steps forming the main pathway up and down stairs. # Guard Protective barrier along stair edges to prevent accidents during use. # Landings (Platforms) Provided at turns where passengers need to pause, these are wide enough as the stairs themselves with an adequate 1000mm length. # Step Combination of riser and tread on which footsteps occur. # Rise Vertical distance measured between floors in a staircase. # Run Total horizontal distance of stairs including landings. # Riser Vertical face or step's upward portion, typically its height is the vertical distance to the next tread. # Tread Horizontal surface or step's downward section. # Nosing Tread extension beyond the riser below providing safety support. # Soffit Underside of a stair forming structural protection. # Railing Framework providing handrails while safeguarding users from accidents. The staircase's structural design is a complex task that requires careful consideration of various factors, including the type of span and deflection considerations. ===== Supports are necessary on both sides of the flight when spanning transversely, while longitudinal spans require deflection analysis to determine waist thickness. In simple systems, stresses produced by longitudinal thrust are small and generally neglected in design. The staircase's dimensions are 1160mm wide, with a concrete cover of 25mm and an imposed load of 4 kN/m². The structural idealization shows a waist thickness of 200mm and a depth of riser of 150mm. Gravity loads are applied in the global y-direction, and the load at the waist is converted to this direction using the angle of inclination. This results in a UDL from the waist of 4.124 kN/m², with a total dead load on the flight area of 7.199 kN/m². Variable loads on the staircase are also considered, including the live load of 4 kN/m². The load on the landing is calculated as 14.370 kN/m² at ultimate limit state. Design calculations show that the ultimate bending moment diagram due to ultimate loads is a critical factor in determining the required reinforcement. For this particular case, a design moment M_{Ed} of 41.119 kNm is used, resulting in a minimum area of steel required of approximately 639.96 mm²/m. The provided reinforcement meets the required standards, and the modification factor β_s is calculated to account for any potential issues with σ_s ; the calculation of deflection and ultimate shear force is ok. ===== Shear reinforcement can be ignored as $VR_{d,c} > V_{Ed}$. ===== To download the full paper in PDF format, click HERE ===== A concrete staircase serves an essential function, connecting different levels of a building while also becoming a significant architectural element. ===== The design of a reinforced concrete staircase is crucial to ensure that it seamlessly fits the surrounding environment and the functional needs of the building. ===== The rise and run ratio is one of the fundamental principles in the design of reinforced concrete staircases, ensuring safety, comfort, and compliance with design standards. ===== To calculate the total rise and run, use the following formulas: $R = H/N$ and $R = L/N$, where R represents the vertical distance (rise) between two consecutive steps and the depth (run) of each step. ===== According to Blondel's formula, the ideal rise and run ratio should be $2R + R = 62/64$ cm, resulting in an ideal rise of approximately 16 cm and an ideal run of 30 cm. Accessible and Sustainable Reinforced Concrete Staircase Design ===== For staircases used both indoors and outdoors, there are various design options available. One popular choice is the sloping slab stair, which features inclined steps ideal for areas with limited space. The structure must be carefully designed to ensure stability and safety. Knee-beam stairs offer additional support and stability by incorporating a horizontal element into the staircase's design. ===== Looking at modern staircase designs, it's clear that innovation plays a key role in creating functional and aesthetically pleasing spaces. One area of focus is internal staircase design, which should blend seamlessly into the surrounding environment while meeting building needs. # Executive Table: Staircase Design Details A reinforced concrete staircase requires careful consideration to ensure smooth integration with the surroundings and adequate functionality. Key aspects include rise and run ratios, accessibility features, and architectural style. # Rise and Run Ratio The ratio of vertical distance (rise) to step depth (run) is fundamental in defining a safe and comfortable staircase design. Calculations must consider this balance to meet design standards. A commonly used formula by architect Francois Blondel provides a foundation for optimal ratios: $2R + R = 62/64$ cm. This suggests an ideal rise and run values of approximately 16 cm and 30 cm, respectively. # Accessibility and Safety Staircase design must prioritize accessibility and safety for all users, regardless of physical abilities. Features like handrails, non-slip steps, adequate lighting, and sufficient width ensure smooth passage. Compliance with local building regulations is also essential to meet minimum safety standards. # Harmony with the Environment A well-designed reinforced concrete staircase should harmoniously integrate into its surroundings, taking into account material, color, and style. This balance between form and function creates a cohesive building design that showcases the staircase as an integral element. # Compliance with Building Regulations Compliance with national building regulations is critical in reinforcing concrete staircase design. These guidelines establish minimum requirements for safety and accessibility, ensuring that architects and engineers prioritize these aspects during project development. # Materials and Construction Techniques The selection of materials and construction techniques also plays a vital role in determining the overall success of a reinforced concrete staircase design. Paraphrased text here ===== The structural integrity of reinforced concrete staircases is heavily reliant on the quality of the concrete used and the strategic placement of reinforcements to ensure a safe and durable staircase over time. Design calculations show that the ultimate bending moment diagram due to ultimate loads is a critical factor in determining the required reinforcement. For this particular case, a design moment M_{Ed} of 41.119 kNm is used, resulting in a minimum area of steel required of approximately 639.96 mm²/m. The provided reinforcement meets the required standards, and the modification factor β_s is calculated to account for any potential issues with σ_s ; the calculation of deflection and ultimate shear force is ok. ===== The ratio of rise to tread on stairs increases as the slope steepens, with a minimum of three risers per flight being recommended. When designing stairs, it's crucial to consider the theoretical procedures for structural analysis, which involves idealising the structure into a line and including additional reinforcement to mitigate cracking at high-stress points. The actual stress distribution in a staircase differs from the calculated one due to its 'three-dimensional' nature and the stiffening effect of triangular tread areas, highlighting the need to account for these factors when detailing the structure. In simple straight flights, supports can be provided on both sides of the flight by walls or stringer beams. When spanning transversely, the waist thickness should not exceed 60mm, while longitudinally, deflection considerations determine the waist thickness. The design requirements for beams and slabs apply to staircases as well, but complex systems cannot be expected to determine deflections without computational analysis. BS 8110 deals with simple types, allowing a modified span/effective depth ratio. A full structural analysis of the staircase is required using EC2, taking into account factors such as concrete density, compressive strength, yield strength, and imposed load. The idealisation of the staircase involves calculating the stresses produced by longitudinal thrust, which are generally neglected in simple designs. The ultimate shear force diagram and shear force equation are provided below: A little consideration will show that it is best to use the design moment $M_{Ed} = 41.119 \text{ kNm}$ to design the entire stairs. $M_{Ed} = 41.119 \text{ kNm} = b - Cc - \phi/2$ Assuming $\phi/2$ mm bars will be used for the construction $d = 200 - 25 - 6 = 169\text{mm}$; $b = 1000\text{mm}$ (designing per unit width); $k = M_{Ed}/(f_{ck}bd^2) = (41.119 \times 106)/(30 \times 1000 \times 169^2) = 0.0479$ Since $k < 0.167$ No compression reinforcement required; $z = d[0.5 + \sqrt{(0.25 - 0.882 \times 0.0479)}] = 0.95d$ $A_{s1} = M_{Ed}/(0.87fykz) = (41.119 \times 106)/(0.87 \times 460 \times 0.95 \times 169) = 639.96 \text{ mm}^2/m$ Provide Y12mm @ 150mm c/c BOT (As,prov = 753 mm²/m) To calculate the minimum area of steel required; $f_{ctm} = 0.3 \times f_{ck}(2/3) = 0.3 \times 30/23 = 2.896 \text{ N/mm}^2$ (Table 3.1 EC2) $A_{s,min} = 0.26 \times f_{ctm}/f_{yk} \times b \times d = 0.26 \times 2.896/460 \times 1000 \times 169 = 276.631 \text{ mm}^2/m$ Check if $A_{s,min} < 0.0013 \times b \times d$ ($219.7 \text{ mm}^2/m$) Since, $A_{s,min} = 276.631 \text{ mm}^2$, the provided reinforcement is adequate. $k = 1.0$ for simply supported beams and slab $\rho = A_s/bd = 753/(1000 \times 169) = 0.004455 < 10\text{-}3/30$ Since $\rho < \rho_0$ $L/d = k[11 + 1.5\sqrt{(f_{ck})\rho/p} + 3.2\sqrt{(f_{ck})\rho/p} - 11.5)]/d = 1.0[11 + 1.5\sqrt{30 \times (0.005477/0.004455)} + 3.2\sqrt{30 \times (0.005477/0.004455)} - 11.5] = 1.0(21.1 + 1.9258) = 23.0258$ Modification factor $\beta_s = 310/(\sigma_{s,req}/(500A_s,prov)) = (310 \times 460 \times 639.96)/(500 \times 753) = 242.358 \text{ N/mm}^2$ $\beta_s = 310/242.358 = 1.2789$ Taking the distance between supports as the effective span, $L = 4.35m$ The allowable span/depth ratio = $\beta_s \times 23.0258 = 1.2789 \times 23.0258 = 29.460$ Actual deflection $L/d = 4350/169 = 25.739$ Since $25.739 < 29.460$, deflection is ok. Ultimate shear force $V_{Ed} = 35.358 \text{ kN} = V_{Ed}/bd = (35.358 \times 1000)/(1000 \times 169) = 0.209 \text{ N/mm}^2$ $VR_{d,c} = [CR_{d,c}k(100\rho f_{ck})^{1/3}] \geq (V_{min})/CR_{d,c} = 0.18/\gamma_c = 0.18/1.5 = 0.12k = 1 + \sqrt{(200/d)} = 1 + \sqrt{(200/169)} = 2.087 > 2.0$, therefore, $k = 2$ $V_{min} = 0.035k1.5f_{ck}0.5V_{min} = 0.035 \times 21.5 \times 300.5 = 0.5422 \text{ N/mm}^2$ $\rho_1 = A_s/bd = 753/(1000 \times 169) = 0.0044556 < 0.02VR_{d,c} = [0.12 \times 2(100 \times 0.0044556 \times 30)^{1/3}] = 0.569 \text{ N/mm}^2$ Since $VR_{d,c} > V_{Ed}$, no shear reinforcement is required. Shear is ok